

Ref.

50925

Colección / Collection / Collection	Technical Indoor. PRO Professional LED
Descripción / Description / Description	Downlight LED Direccional Downlight LED Directional Downlight LED Orientable

**Características Luminaria / Light Data Sheet /
Caractéristiques de la Luminaire**

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	Cristal / Glass / Verre		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Transparente / Transparent / Transparent		
Colores / Colours / Couleurs	01 Negro / Black / Noir (in 3000K) 90 Blanco Técnico / Technical White- / Blanc Technique		
Vatios / Watts / Watts	25W		
Lúmens / Lumens / Lumens	Color T. ^a	Useful Lm	Chip Lm
	3000K	2097 lm	-
	4000K	2147 lm	2768 lm
Grados Apertura / Opening Angle / Angle d'ouverture	17°		
IP	20		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids	0,85 Kg		
Cantidad / Pieces / Quantité	1/ 12		

Características del Chip / Chip Data Sheet / Caractéristiques de la Puce

Marca / Brand / Marque	EDISON
Tipo / Type / Type	COB
L70 B10	50.000 h
SDCM (Mac Adam)	3
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	111 Lm/W (4000K)



Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur


Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
50925-298_-	ON-OFF. Non Dimmable	AC100-240V 50/60Hz	>0,9	3	600 mA	Not Free
50925-238_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	600 mA	Free
50925-518_-	Dimmable. Trailing Edge (20W)	AC220-240V 50/60Hz	>0,9	5	600 mA	Free
50925-C98_-	Dimmable. SMART CONTROL	AC100-265V 50/60Hz	>0,95	5	600 mA	Free
50925-478_-	Dimmable. 1-10V / DALI / PUSH	AC200-240V 50/60Hz	>0,95	5	600 mA	Free

Colores / Colours / Couleurs



90 Blanco Técnico / Technical White
/ Blanc Techniqué

Accesorios / Accessories / Accessoires



JISO Smart Control

2DCLEDK1

2DCLEDK2

Productos Relacionados / Related Products / Produits Associés



50915



50930

Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

http://www.jisoiluminacion.es/CE/CE_RECESSED-LUMINAIRES.pdf

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

<http://www.jisoiluminacion.es/Instrucciones/Instrucciones-Empotrables-Generico-ES-EN.pdf>

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

http://www.jisoiluminacion.es/Ficheros_LDT/50925.ltd.zip

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

http://www.jisoiluminacion.es/Ficheros_IES/50925.IES.zip